



ISOLMANT PIOMBO

■ DESCRIPTION

Product composed of 2 layers of Isolmant 3 mm with a 0.35 mm or 0.50 mm lead sheet in the middle.

■ THICKNESS

Approx. 6.5 mm.

■ SOUNDPROOFING

Lead 0.35 mm - airborne noise abatement: $R_w = 26$ dB; (assessment index ISO 500 Hz calculated on the frequency band from 100 to 5000 Hz).

■ ROLL DIMENSIONS

- 1 m x 3 m = 3 m² without individual box (120 m² pallet).
- 1 m x 3 m = 3 m² with individual box (90 m² pallet).

isolmant Piombo

WARNING:

This technical data sheet is not a valid specification. It is up to the user to establish whether the product is suitable for the intended use.

FIELDS OF USE

Thanks to its technical performance qualities, Isolmant Piombo is particularly recommended for soundproofing bathroom floors, and for soundproofing pipes and drainpipes, while performing anti-vibration and anti-condensation functions. It is also recommended for soundproofing load-bearing pillars and lining electric boxes.

SPECIFICATION

Insulating material composed of two 3 mm layers of closed-cell, physically cross-linked polyethylene foam with a lead sheet of mm (0.35/0.50 mm). Total thickness: approximately 6.5 cm.

NEW OFFICES!



bigger, more services

TECNASFALTI

Via dell'Industria 12, Località Francolino
20080 Carpiano (Mi) Tel. +39 02 9885701
Fax +39 02 98855702 clienti@isolmant.it
www.isolmant.it