



## ISOLMANT PERFETTO TR

### Traspirante



#### THICKNESSES

30, 50, 80 mm approx. (in warehouse).

On request (for at least 300 m<sup>2</sup> and with 10 working days' notice), it is possible to also request the following thicknesses: 35, 40, 45, 55, 60, 65, 70, 75, 85, 90, 95, 100, 105, 110, 115, 120 mm.

#### THERMAL RESISTANCE AND SPECIFIC HEAT

Isolmant Perfetto TR 30  $R_t = 0.85 \text{ m}^2 \text{ K/W}$   $c = 0.24 \text{ kJ/kgK}$ .

Isolmant Perfetto TR 50  $R_t = 1.40 \text{ m}^2 \text{ K/W}$   $c = 0.24 \text{ kJ/kgK}$ .

Isolmant Perfetto TR 80  $R_t = 2.26 \text{ m}^2 \text{ K/W}$   $c = 0.24 \text{ kJ/kgK}$ .

#### SOUNDPROOFING POWER

Currently being certified.

#### VAPOUR PERMEABILITY

$\mu = \text{approx. } 2$ .

#### FORMAT

In 1 m x 2.85 m = 2.85 m<sup>2</sup> panels. On request (for at least 300 m<sup>2</sup> and with 10 working days' notice), it is possible to also request non-standard heights.

#### PACKAGING

Packs of 10-7-5 panels for Perfetto TR 30-50-80 (respectively).

## isolmant TR

PERFETTO

#### WARNING:

This technical data sheet is not a valid specification. It is up to the user to establish whether the product is suitable for the intended use.

#### FIELDS OF USE

Isolmant Perfetto TR is a versatile product recommended for the soundproofing and thermal insulation of vertical breathable partitions, both perimetric and dividing various property units.

Isolmant Perfetto TR can be inserted into air gaps while building the second wall (glued or anchored if necessary). It guarantees a high level of noise abatement, even when used with false plasterboard walls or lightweight plasterboard walls on metal frameworks.

#### SPECIFICATION

Insulating layer in floor-to-ceiling panels (100x285 cm) composed of a layer of technical textile fibre, with high levels of soundproofing power and excellent thermal resistance. Thickness ..... mm (30, 50 or 80 mm). Thermal resistance of the panel equal to .... m<sup>2</sup>K/W (0.85, 1.40 or 2.26 m<sup>2</sup>K/W for the 30, 50 or 80 mm versions respectively).

NEW OFFICES!



bigger, more services

#### TECNASFALTI

Via dell'Industria 12, Località Francolino  
20080 Carpiano (Mi) Tel. +39 02 9885701  
Fax +39 02 9885702 clienti@isolmant.it  
[www.isolmant.it](http://www.isolmant.it)