



ISOLMANT FASCIA TAGLIABATTISCOPA



Polyethylene foam adhesive strips available in two versions: 1 cm or 3 cm wide. The 3 cm version comes in two shades: anthracite grey and light grey. 1.2 mm (for the 1 cm version) or 3 mm (for the 3 cm version).

■ THICKNESS

3 mm

■ SOUNDPROOFING

Not using Isolmant Fascia Taglia Battiscopa causes an acoustic bridge to be formed, which may result in the loss of many decibels.

■ METHODS OF USE

- After laying and grouting the floor and trimming off the excess from the perimeter strip, the TBTS strip is laid.
- After stripping the adhesive part, continue with laying, ensuring perfect adhesion to the wall, where the skirting board will be attached.
- Glue on the skirting board, attaching it completely to the Fascia TBTS, avoiding rigid connections with the floor.
- Trim off the excess TBTS strip protruding from the skirting board and seal any gaps with elastic materials (silicones or elasticised mortars).

■ PACKAGING

5 reels of 20 linear m/each for a total of 100 linear m.

isolmant FasciaTBTS

WARNING:

This technical data sheet is not a valid specification. It is up to the user to establish whether the product is suitable for the intended use.

FIELDS OF USE

To ensure the floating floor is fitted correctly, it is necessary for the whole system resting on the mat to be able to move freely.

This is why it is also essential to separate the skirting board or ceramic coating from the surface finish. Any rigid connection caused by gaps in the skirting board mortar may cause a loss of soundproofing against impact noise of several decibels.

SPECIFICATION

Polyethylene foam adhesive strips to separate the skirting board from the inishing floor.

Thickness 3 mm, width 3 cm.

Colour (light grey or anthracite grey).

NEW OFFICES!



bigger, more services

TECNASFALTI

Via dell'Industria 12, Località Francolino
20080 Carpiano (Mi) Tel. +39 02 9885701
Fax +39 02 98855702 clienti@isolmant.it
www.isolmant.it